

TECHNICAL SPECIFICATIONS

Zellabox™ can accommodate your requirements based on a plug n play operation of the following components:

- Power Distribution Unit (PDU)
- Cooling System
- Uninterruptible Power Supply (UPS)
 - Rack Mounted
- Access Control System (Code)
- Environmental Monitoring
- Automated Fire Extinguishing System
 - Clean Agent



STANDARD MODEL - Cubb®		25U	30U (3KVA UPS)	30U (6KVA UPS)	38U	
CABINET						
Dimensions	Height	mm	1660	2020	2020	2250
	Width	mm	685	685	685	685
	Depth	mm	895	895	895	895
	Weight	kg	225	240	293	308
Client available space	U		17	22	19	27
Fire extinguishing system - Pyrorack™	Mag		2	2	2	2
PDU (including current meter)	V/Ph/Hz		240/1/50	240/1/50	240/1/50	240/1/50
UPS	kVA		3	3	6	6
Cooling system	Btu/KW		9000/2.6	12000/3.5	12000/3.5	12000/3.5
Condensate pump head	M (Max)		8	8	8	8
Switchboard	AMP		24	24	40	40
Access control			Digipad	Digipad	Digipad	Digipad
Lights - 12V LED	Quantity	No	2	2	2	2
OPTIONAL EXTRAS						
Biometric Access						Fingerprint
Web Camera						Snake-eye
Fabrication						Stainless Steel
Colour						On request
Electrical	Phase					Single / 3
Bypass Switch						Rack Mounted
Rack Monitor						Remote Power Manager
ON-SITE REQUIREMENTS						
Cooling System Inter-connecting		M (Max)				20 Horizontal
Pipe work and Control Wiring						15 Vertical
Condensate Drain Pipe		DIA				9mm ID / 16mm OD PVC

TECHNICAL SPECIFICATIONS

Zellabox™ can accommodate your requirements based on a plug n play operation of the following components:

- Power Distribution Unit (PDU)
- Cooling System
- Uninterruptible Power Supply (UPS)
 - Rack Mounted
- Access Control System (Code)
- Environmental Monitoring
- Automated Fire Extinguishing System
 - Clean Agent



DUAL COOLING MODEL - CubbDuo®		25U	30U (3KVA UPS)	30U (6KVA UPS)	38U	
CABINET						
Dimensions	Height	mm	1790	2150	2150	2380
	Width	mm	685	685	685	685
	Depth	mm	895	895	895	895
	Weight	kg	265	280	333	348
Client available space	U	17	22	19	27	
Fire extinguishing system - Pyrorack™	Mag	2	2	2	2	
PDU (including current meter)	V/Ph/Hz	240/1/50	240/1/50	240/1/50	240/1/50	
UPS	kVA	3	3	6	6	
Cooling system	Quantity	No	2	2	2	
	Btu/KW	9000/2.6	12000/3.5	12000/3.5	12000/3.5	
Condensate pump head	M (Max)	8	8	8	8	
Switchboard	AMP	32	32	55	55	
Access control		Digipad	Digipad	Digipad	Digipad	
Lights - 12V LED	Quantity	No	2	2	2	
OPTIONAL EXTRAS						
Biometric Access				Fingerprint		
Web Camera				Snake-eye		
Fabrication				Stainless Steel		
Colour				On request		
Electrical	Phase			Single / 3		
Bypass Switch				Rack Mounted		
Rack Monitor				Remote Power Manager		
ON-SITE REQUIREMENTS						
Cooling System Inter-connecting	M (Max)			20 Horizontal		
Pipe work and Control Wiring				15 Vertical		
Condensate Drain Pipe	DIA			9mm ID / 16mm OD		
				PVC		